

MUNICIPAL FIRE HOSE

ANGUS  
FIRE



HI-COMBAT II

Hi-Combat II aggressive interior attack hose features the “IdentiFire” information system, allowing fire departments to permanently add their name and NFPA test information. Hi-Combat IIR was designed to address situations where the interior attack hose is used as a lifeline. With reflective material woven right into the hose, firefighters and civilians can follow the reflective <Exit> and <Arrows> to safety. Hi-Combat 2 1/2" provides big flows supporting master streams and portable monitors. With all the benefits of traditional Hi-Combat including reduced friction loss, better abrasion resistance and better puncture resistance it is the ideal big line for high-rise fire fighting.

\*Note 2 1/2" R available with reflective stripe only.

ITEM#	HOSE SIZE (INCH)	SERVICE PRESSURE (PSI)	PROOF PRESSURE (PSI)	BURST PRESSURE (PSI)	BOWL SIZE (INCH)	50' WEIGHT UNCOUPLED (LBS)	50' COIL DIAMETER (INCH)
ANGUSHCII134	1 3/4" II	500	1000	1500	2 1/8"	18 lbs.	16 1/2"
ANGUSHCIIR134	1 3/4" IIR	500	1000	1500	2 1/8"	18 lbs.	16 1/2"
ANGUSHCII212	2 1/2"	400	800	1200	2 7/8"	23 lbs.	18 1/2"
ANGUSHCIIR212	2 1/2" R*	400	800	1200	2 7/8"	23 lbs.	18 1/2"

FIREPOWER II



Firepower II has an extruded-through-the-weave rubber inner jacket, incorporating kink resistance, heat resistance and low friction loss into an affordable hose. Firepower II has a kink loop of less than 11 inches when charged at only 50 psig. The rubber encapsulated inner jacket offers over 6 times the heat resistance of ordinary double jacket hoses. The rubber encapsulated inner hose will withstand bursting, even when punctured.

Construction

Outer jacket: Woven synthetic jacket – complete with Hypa-Lock® coating to increase abrasion resistance and inhibit water pick-up of outer yarns.

Inner jacket: Extruded-through-the-weave rubber hose.

ITEM#	HOSE SIZE	SERVICE TEST	PROOF PRESSURE	BURST	BOWL SIZE	50' WEIGHT UNCOUPLED
ANGUSFP11/2X50	1 1/2"	400	1000	1500	1 15/16"	14 lbs.
ANGUSFP13/4X50	1 3/4"	400	1000	1500	2 1/8"	15 lbs.
ANGUSFP21/2X50	2 1/2"	400	850	1300	3"	27 1/2 lbs.



HI-VOL 300

Hi-Vol 300 is a series of high pressure large diameter through-the-weave high pressure attack lines designed to meet the NFPA requirements for attack hose. These hoses in 3", 4", and 5" have all the benefits of a rubber covered hose and can be operated at pressures up to 300 psi (2100 kPa).

ITEM#	HOSE SIZE (INCH)	SERVICE PRESSURE (PSI)	PROOF PRESSURE (PSI)	BURST PRESSURE (PSI)	BOWL SIZE (INCH)	50' WEIGHT UNCOUPLED (LBS)	50' COIL DIAMETER (INCH)
ANGUSHV3003X50	3"	300	600	900	3 13/32"	37.5 lbs.	18 3/8"
ANGUSHV3004X50	4"	300	600	900	4 9/16"	47.5 lbs.	18"
ANGUSHV3005X50	5"	300	600	900	5 3/8"	67.5 lbs.	19"