



Geysers III Classic

### GEYSER III CLASSIC

**Models C2300 & C2310**

- Heavy duty 1/6 HP, 115 volt motor
- Epoxy coated aluminum body resists heat, oil and corrosion
- Open type trash impeller resists clogging
- Removable screen for easy cleaning
- 1 1/4" NPT discharge with brass fitted garden hose adapter
- Pumps water down to within 3 mm of floor
- TWO YEAR warranty
- Weighs only 10 lbs.

DISCHARGE HEIGHT ABOVE PUMPING LEVEL	0'	5'	10'	15'	20'	25'
Gallons per minute	25	21	17	15	9	3

### 115 VOLT PORTABLE MINI-VAC

**Model CM40**

Pushes water 35 feet high – Pumps up to 360 gallons per hour

- Non-corrosive pump end with stainless steel wear plates
- Inlet and outlet fitted for standard garden hose
- 115 volt motor protected by internal thermal overload
- Air cooled, high torque motor with replaceable brushes
- New, more efficient design – UL Listed
- Grounded 6' power cord and plug

DISCHARGE HEIGHT ABOVE PUMPING LEVEL	0'	10'	20'	30'	40'
Gallons per minute	10	6	4	2.3	0.5



Portable Mini-Vac

**Model CM40P**

- "Pud-L-Scoop" and 6' suction hose included on M40P model – pumps floors dry to 1/8"

### 12 VOLT PORTABLE BLUE WATER PUMP

**MODELS BW85 & BW85P**

**Features same as Model CM40A:**

- "Pud-L-Scoop" and 6' suction hose included on BW85P model only – pumps floors dry to 1/8"
- 10' electric cable leads with in-line switch and color coded battery clamp



Portable Blue Water Pump

MODEL	DISCHARGE HEIGHT ABOVE PUMPING LEVEL	0'	10'	20'	30'	40'	RE-PLACEMENT IMPELLER KIT	PUMP END KIT
BW85/BW85P/8524	Gallons per minute	10	8.5	6.8	4.4	3.0	A270	A267

### CONTROLS



Model SSS-11



Model NM15K/  
NM16K

**Liquid Level Control – Model SSS-11 (10 ft.)**

- Patented solid state design
- Use with sump or utility pumps
- Use to actuate water level alarms
- Mounts anywhere – on pump, on wall, etc.
- For use in small sumps where floats will not fit
- Use to detect or pump very small levels of water
- Rated at 120 VAC, 60 Hz, 12 AMPS, 1/2 HP max.

**Geyser® Conversion Kit (GCK) Contains:**

- SSS-11 Solid State Switch, Mud Pad, Check Valve

**Float Switch Models – NM15K, NM16K**

- Rated at up to 15 AMPS
- Piggy-back plug connection for 115 volt operation and with 8' power cord (NM15K, NM16K0)
- Ideal for any sump pump
- NM15K normally open – for maintaining vessels empty
- NM16K normally closed – for maintaining vessels full
- Mounting straps included